



## Technical data sheet

### OPEN CHAMBER GWH LOW NOX



**Includes:  
Outlet pipe  
gas kit**



High DHW production



No pilot flame



Super Slim



Solar compatible



Oxygen-free copper heat exchanger



Outlet gas pipe kit included (C13, C33)



5 NOx Class

MODEL		EMLCLE11NOXGN	EMLCLE11NOXGLP
<b>POWER</b>			
Power supply	<b>V, P, HZ</b>	220-240V (1 Phase~ 50Hz)	220-240V (1 Phase~ 50Hz)
Input power	<b>kW</b>	22	22
Useful power	<b>kW</b>	19,4	19,4
Minimum input power	<b>kW</b>	7,5	7,5
Minimum output power	<b>kW</b>	6,1	6,1
Efficiency	<b>%</b>	≥ 88%	≥ 88%
Declared profile	<b>-</b>	M	M
Energy classification	<b>-</b>	A	A
<b>PERFORMANCE</b>			
Type of gas	<b>-</b>	Natural Gas G20	Butane Gas G30 / Propane G31
Combustion	<b>-</b>	Closed chamber	Closed chamber
Ignition	<b>-</b>	Electronic Automatic	
Gas pressure	<b>Mbar</b>	20	28 - 30 / 37
<b>TYPE OF HEATER</b>			
Maximum pressure	<b>bar</b>	10	10
Minimum pressure	<b>bar</b>	0,2	0,2
Maximum flow rate	<b>L/min</b>	11,3	11,3
Minimum flow rate	<b>L/min</b>	8	8
Water temperature	<b>°C</b>	35 ~ 65	35~65
<b>DIMENSIONS AND WEIGHT</b>			
Dimensions (W×H×D)	<b>mm</b>	345×570×150	345×570×150
Weight	<b>Kg</b>	12,3	12,3
<b>CONNECTIONS</b>			
Gas connection	<b>-</b>	G1/2"	G1/2"
Cold water connection	<b>-</b>	G1/2"	G1/2"
Hot water connection	<b>-</b>	G1/2"	G1/2"
Ø Gas outlet	<b>mm</b>	Ø 60/100	Ø 60/100
Gas outlet length	<b>m</b>	0,5 - 3	0,5 - 3
EAN CODE		8435483810310	8435483810303