

Emelson

DHW RANGE

3 YEARS
WARRANTY
TOTAL
QUALITY COMMITMENT

M PROFILE

A ACS



Technical data sheet

OPEN CHAMBER GWH LOW NOX NOVO

11
L/min
High DHW production

No pilot flame

Super slim

LED
Led Display

Gas and temperature sensor

Multiple protection

Forced draught accessory included (B23, B53)

LOW NOX
5x
5 NOx Class

MODEL

		EML-CLA-11NOXNOVOGN	EML-CLA-11NOXNOVOGLP
POWER			
Input power	kW	22	22
Useful power	kW	18,5	18,5
Minimum input power	kW	7,5	7,5
Minimum output power	kW	6,8	6,8
Efficiency	%	79	79
Declared profile	—	M	M
Energy classification	—	A	A
PERFORMANCE			
Type of gas	—	Natural Gas G20	Butane Gas G30 / Propane G31
Combustion	—	Open chamber	Open chamber
Ignition	—	Automatic + battery	Automatic + battery
Gas pressure	Mbar	20	30 / 37
Voltage	Vdc	3	3
TYPE OF HEATER			
Maximum pressure	bar	10	10
Minimum pressure	bar	0,5	0,5
Maximum flow rate (2BAR)	L/min	10,7	10,7
Minimum flow rate	L/min	5	5
Water temperature	C°	35 ~ 85	35 ~ 85
DIMENSIONS AND WEIGHT			
Net dimensions (W×H×D)	mm	330x679x213	330x679x213
Gross dimensions (W×H×D)	mm	400×790×280	400×790×280
Net weight	Kg	10,5	10,5
Gross weight	kg	12,2	12,2
CONNECTIONS			
Gas connection	—	G1/2"	G1/2"
Cold water connection	—	G1/2"	G1/2"
Hot water connection	—	G1/2"	G1/2"
Ø Gas outlet	Ø mm	Ø 110	Ø 110
Max. length of gas outlet	mm	350	350
Max. number of elbows	mm	2.000	2.000
EAN CODE		8435483835535	8435483818545