

Emelton

AQUA RANGE

3 YEARS WARRANTY
TOTAL QUALITY COMMITMENT

5 YEARS WARRANTY
TANK QUALITY COMMITMENT

B ACS



Technical data sheet

VERTICAL ELECTRIC WATER HEATER COMFORT



Incoly 840 resistance

High density polymethane insulation

Electrolytic sleeves

Magnesium anode

Dry overheating protection

Sapphire enamelled tank

MODEL		EML-TV-15COM	EML-TV-30COM	EML-TV-50COM	EML-TV-80COM	EML-TV-100COM
Power supply	V,Ph,HZ	220-240V (1 Phase~ 50/60Hz)				
POWER						
Power	W	1500	1500	1500	1500	1500
Current	A	6,5	6,5	6,5	6,5	6,5
Declared profile	-	S	S	L	L	L
Energy classification	-	C	B	C	C	C
PERFORMANCE						
Capacity	L	15	30	50	80	100
Maximum working pressure	Mpa	0,75	0,75	0,75	0,75	0,75
Operating temperature	°C	30~75	30~75	30~75	30~75	30~75
Recovery time 15-40 °C	-	25 min	35 min	1h 5 min	1h 35 min	1h 56 min
FEATURES						
Insulation thickness	mm	20	20	20	20	20
Material thickness	mm	2	1,8	1,8	2,0	2,0
Type of coating	-	Enamelled sapphire coating				
Degree of protection	-	IPX4	IPX4	IPX4	IPX4	IPX4
Anode	Type	Magnesium				
	Size	mm	Ø20x300	Ø20x300	Ø20x300	Ø20x300
Resistance	-	Incoloy 840 submerged				
Type of installation	-	Vertical				
Water inlet pipe	-	G1/2"				
DIMENSIONS AND WEIGHT						
Net dimensions (ØxH)	mm	Ø380x386x305	Ø340x618	Ø380x735	Ø450x808	Ø450x963
Net weight	Kg	9	13,6	17,5	23,7	26,9
EAN code	-	8435483828773	8435483828780	8435483828797	8435483828803	8435483828810

EMELTON reserves the right to modify models and technical data without prior notice. Information valid except for typographical or printing errors.

5 años de garantía en la cuba
(performing required maintenance)